

View Online at <https://aerobasegroup.com/nsn/5306-00-338-0411>

Threads Per Inch:

24 counterbore

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.575 inches

Fastener Length:

4.100 inches

Head Style:

Hexagon

Head Height:

0.320 inches

Width Between Flats:

Between 0.928 inches and 0.940 inches

Shoulder Diameter:

Between 0.6395 inches and 0.6400 inches

Shoulder Length:

Between 3.325 inches and 3.355 inches

Shank Unthreaded Hole Diameter:

0.143 inches first hole and 0.149 inches first hole

Concentric Hole Depth:

0.700 inches

Concentric Hole Diameter:

Between 0.338 inches and 0.345 inches

Internal Thread Length:

0.450 inches counterbore

Thread Diameter:

0.625 inches

Thread Series:

Unjf counterbore

Internal Thread Direction:

Right-hand counterbore

Thready Qty Per Inch (tpi):

18

Thread Size:

0.375 inches counterbore

Criticality Code Justification:

Aavh

Distance From Head Largest Bearing Surface To Shank Hole Center:

3.975 inches first hole

Internal Thread Class:

3b counterbore

Material:

Steel comp xm-13

Surface Treatment:

Cadmium

Surface Treatment Specification:

Lc+77-1061 36659 mfr ref single treatment response

Style Designator:

Counterbore threaded

Test Data Document:

36659-lc+72-1076 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0