## NSN 5306-00-338-4104

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-338-4104 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.536 inches and 0.603 inches **Fastener Length:** Between 2.358 inches and 2.405 inches **Head Style:** Double hexagon **Head Height:** Between 0.271 inches and 0.291 inches Width Between Flats: Between 0.741 inches and 0.752 inches **Grip Diameter:** Between 0.4982 inches and 0.4991 inches **Thread Diameter:** 0.500 inches **Grip Length:** Between 1.802 inches and 1.822 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 260000 pounds per square inch Hardness Rating: 51.0 rockwell c and 54.0 rockwell c Material: Steel comp h11 **Material Specification:** Ams 6845 assn standard single material response or sps-m-107, fscm 26512 mfr ref single material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Mil-c-8837, type 1, cl 2 military specification single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:** 

No

**Demilitarization:** 

## NSN 5306-00-338-4104

Shear Bolt - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

Mil-c-8837 spec.