NSN 5306-00-339-5513

Internally Relieved Body Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-339-5513 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.369 inches **Fastener Length:** 3.125 inches **Head Style:** Hexagon **Head Height:** 0.156 inches Width Between Flats: 1.125 inches **Shoulder Diameter:** Between 0.870 inches and 0.872 inches **Shoulder Length:** 2.645 inches **Shank Unthreaded Hole Diameter:** 0.141 inches first hole **Concentric Hole Diameter:** 0.312 inches **Thread Diameter:** 0.625 inches Thready Qty Per Inch (tpi): 18 Min. Tensile Strength (psi): 180000 pounds per square inch Distance From Head Largest Bearing Surface To Shank Hole Center: 2.957 inches first hole and 2.988 inches first hole Material: Steel comp 4140 **Surface Treatment:** Cadmium **Surface Treatment Specification:** Qq-p-416 federal specification single treatment response **Style Designator:** Concentric hole unthreaded **Thread Series Designator:**

Unf Shelf Life: N/a

NSN 5306-00-339-5513

Internally Relieved Body Bolt - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МЛО	201	ure:

--

Demilitarization:

No

Fiig:

A003b0