## NSN 5306-00-340-4714

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-340-4714

#### Thread Class:

3a

**Thread Direction:** 

**Right-hand** 

#### Thread Length:

Between 0.298 inches and 0.348 inches

#### Fastener Length:

Between 0.746 inches and 0.776 inches

#### **Head Style:**

Dished hexagon

#### **Head Height:**

Between 0.110 inches and 0.125 inches

#### Width Between Flats:

Between 0.367 inches and 0.376 inches

#### Grip Diameter:

Between 0.1885 inches and 0.1895 inches

**Thread Diameter:** 

0.190 inches

### Grip Length:

Between 0.428 inches and 0.448 inches

#### Thready Qty Per Inch (tpi):

32

#### Min. Tensile Strength (psi):

160000 pounds per square inch

Material:

Iron alloy 660

#### Material Specification:

Ams 5731 assn standard single material response or ams 5737 assn standard single material response

#### Surface Treatment:

Cadmium and chromate

#### Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification all treatment responses

#### Thread Series Designator:

Unjf

#### **Specification Data:**

80205-nas6303 professional/industrial association standard

#### Shelf Life:

N/a

#### Unit Of Measure:

--

#### Demilitarization:

No

# NSN 5306-00-340-4714

Shear Bolt - Page 2 of 2

Fiig: A003b0

