

View Online at <https://aerobasegroup.com/nsn/5306-00-341-7422>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.482 inches

Fastener Length:

3.595 inches

Head Style:

Dee

Head Diameter:

1.375 inches

Head Height:

0.125 inches

Distance From Centerline To Flat:

Between 0.495 inches and 0.500 inches

Shoulder Diameter:

Between 0.873 inches and 0.874 inches

Shoulder Length:

2.975 inches

Shank Unthreaded Hole Diameter:

0.143 inches first hole and 0.148 inches first hole

Concentric Hole Depth:

2.810 inches

Concentric Hole Diameter:

0.562 inches

Thread Diameter:

0.750 inches

Thready Qty Per Inch (tpi):

16

Min. Tensile Strength (psi):

200000 pounds per square inch

Distance From Head Largest Bearing Surface To Shank Hole Center:

3.400 inches first hole

Special Features:

Zinc chromate finish on concentric hole

Material:

Steel

Material Specification:

Mil-s-5626 military specification single material response or ams 6382 assn standard single material response

Surface Treatment:

Cadmium head

Surface Treatment Specification:

Qq-p-416 type 1 federal specification single treatment response threads

Style Designator:

Concentric hole unthreaded

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5626 spec.