## NSN 5306-00-343-1410

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-343-1410

**Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.298 inches and 0.348 inches **Fastener Length:** Between 0.370 inches and 0.400 inches **Head Style:** Hexagon **Head Height:** Between 0.110 inches and 0.125 inches Width Between Flats: Between 0.367 inches and 0.376 inches **Grip Diameter:** Between 0.1885 inches and 0.1895 inches **Thread Diameter:** 0.190 inches **Grip Length:** Between 0.052 inches and 0.072 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch **Surface Finish:** 32.0 microinches threads Material: Iron alloy 660 **Material Specification:** Ams 5731 assn standard single material response or ams 5737 assn standard single material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2, cl 2 federal specification all treatment responses **Thread Series Designator:** Unjf **Specification Data:** 80205-nas6303 professional/industrial association standard

Shelf Life:

**Unit Of Measure:** 

N/a

## NSN 5306-00-343-1410

Shear Bolt - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0