## NSN 5306-00-343-2737

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-343-2737

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 1.487 inches and 1.537 inches
Fastener Length:
Between 6.122 inches and 6.152 inches
Head Style:
Double hexagon w/hole
Head Height:
Between 0.913 inches and 0.933 inches
Width Between Flats:
Between 1.052 inches and 1.064 inches
Extended Washer Diameter:
Between 1.615 inches and 1.625 inches
Extended Washer Thickness:
Between 0.212 inches and 0.232 inches
Grip Diameter:
Between 0.9980 inches and 0.9990 inches
Thread Diameter:
1.000 inches
Grip Length:
Between 4.615 inches and 4.635 inches
Thready Qty Per Inch (tpi):
12
Min. Tensile Strength (psi):
220000 pounds per square inch
Material:
Steel comp h11
Material Specification:
Ams 6487 assn standard single material response
Surface Treatment:
Nickel and cadmium
Surface Treatment Specification:
Ams 2416 assn standard all treatment responses
Thread Series Designator:
Unif
Shelf Life:
N/a
Unit Of Measure:
•

## NSN 5306-00-343-2737

Shear Bolt - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0