## NSN 5306-00-343-2924

Shear Bolt - Page 1 of 2

**Thread Class:** 

Right-hand

**Thread Direction:** 

За



View Online at https://aerobasegroup.com/nsn/5306-00-343-2924

| Thread Length:   |
|--|
| Between 0.892 inches and 0.942 inches                      |
| Fastener Length:   |
| Between 6.339 inches and 6.369 inches                      |
| Head Style:  |
| Double hexagon extended washer                             |
| Head Height:   |
| 0.557 inches   |
| Width Between Flats:                                       |
| Between 0.616 inches and 0.627 inches                      |
| Extended Washer Diameter:                                  |
| Between 0.928 inches and 0.938 inches                      |
| Extended Washer Thickness:                                 |
| Between 0.123 inches and 0.143 inches                      |
| Grip Diameter:   |
| Between 0.5605 inches and 0.5615 inches                    |
| End Application:   |
| W/s: aircraft, galaxy c-5; support equipment, c-5 aircraft |
| Thread Diameter:   |
| 0.562 inches   |
| Grip Length:   |
| Between 5.427 inches and 5.447 inches                      |
| Thready Qty Per Inch (tpi):                                |
| 18   |
| Min. Tensile Strength (psi):                               |
| 220000 pounds per square inch                              |
| Material:  |
| Steel comp h11   |
| Material Specification:                                    |
| Ams 6487 assn standard single material response            |
| Surface Treatment:   |
| Nickel and cadmium   |
| Surface Treatment Specification:                           |
| Ams 2416 assn standard all treatment responses             |
| Thread Series Designator:                                  |
| Unjf   |
| Shelf Life:  |
| N/a  |
|  |

## NSN 5306-00-343-2924

Shear Bolt - Page 2 of 2



|    | • • |             |    |     |      |
|----|-----|-------------|----|-----|------|
| In | 18  | <i>(</i> )+ | МА | 261 | ıre: |
|    |     |             |    |     |      |

--

Demilitarization:

No

Fiig:

A003b0