## NSN 5306-00-354-3167

Close Tolerance Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-354-3167 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.251 inches and 0.301 inches **Fastener Length:** Between 1.636 inches and 1.666 inches **Head Style:** Hexagon **Head Height:** Between 0.110 inches and 0.125 inches Width Between Flats: Between 0.367 inches and 0.376 inches **Grip Diameter:** Between 0.1890 inches and 0.1895 inches **Shank Unthreaded Hole Diameter:** 0.141 inches first hole and 0.151 inches first hole **Thread Diameter:** 0.190 inches **Grip Length:** Between 1.365 inches and 1.385 inches Thready Qty Per Inch (tpi): 32 Distance From Head Largest Bearing Surface To Shank Hole Center: 3.106 inches first hole and 3.156 inches first hole **Surface Finish:** 63.0 microinches bearing surface of head Material: Titanium alloy uns r56400 **Material Specification:** Ams 4928 assn standard single material response **Thread Series Designator:** Unf **Specification Data:** 80205-nas653 professional/industrial association standard Shelf Life: N/a **Unit Of Measure: Demilitarization:** 

No

## **NSN 5306-00-354-3167** Close Tolerance Bolt - Page 2 of 2



Fiig:

A003b0