## NSN 5306-00-362-3707

Eccentric Head Bolt - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5306-00-362-3707

| Thread Class:  |
|--|
| 3a   |
| Thread Direction:  |
| Right-hand   |
| Fastener Length:   |
| 2.375 inches   |
| Head Style:  |
| Double hexagon   |
| Head Diameter:   |
| Between 0.685 inches and 0.688 inches                            |
| Head Height:   |
| 0.250 inches   |
| Distance From Center Of Head To Center Of Shank:                 |
| 0.312 inches   |
| Shank Unthreaded Hole Diameter:                                  |
| 0.109 inches first hole  |
| Internal Drive Style:  |
| W/o internal drive   |
| Thread Diameter:   |
| 0.437 inches   |
| Thready Qty Per Inch (tpi):                                      |
| 20   |
| Min. Tensile Strength (psi):                                     |
| 135000 pounds per square inch                                    |
| Hardness Rating:   |
| 28.0 rockwell c and 31.0 rockwell c                              |
| Distance From Head Largest Bearing Surface To Shank Hole Center: |
| 2.266 inches first hole  |
| Material:  |
| Steel comp 3140  |
| Material Specification:  |
| Sae assn standard single material response                       |
| Thread Series Designator:  |
| Unf  |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |
| No   |
| Filg:  |
| A003b0   |
|  |