

View Online at <https://aerobasegroup.com/nsn/5306-00-369-5635>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.622 inches and 0.672 inches

Fastener Length:

Between 2.507 inches and 2.537 inches

Head Style:

Double hexagon w/hole

Head Height:

Between 0.378 inches and 0.398 inches

Width Between Flats:

Between 0.430 inches and 0.439 inches

Extended Washer Diameter:

Between 0.639 inches and 0.649 inches

Extended Washer Thickness:

Between 0.081 inches and 0.101 inches

Shoulder Diameter:

0.4047 inches first shoulder and 0.4057 inches first shoulder

Shoulder Length:

1.865 inches first shoulder and 1.885 inches first shoulder

Thread Diameter:

0.375 inches

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

220000 pounds per square inch

Shoulder Shape:

Round first shoulder

Material:

Steel comp h11

Material Specification:

Ams 6487 assn standard single material response

Surface Treatment:

Nickel and cadmium and chromate

Surface Treatment Specification:

Stsbs 002, lockheed-georgia co mfr ref all treatment responses

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0