NSN 5306-00-369-5725

Externally Relieved Body Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-369-5725 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.235 inches and 0.285 inches **Fastener Length:** Between 0.900 inches and 0.920 inches **Head Style:** Double hexagon w/hole **Head Height:** Between 0.248 inches and 0.268 inches Width Between Flats: 0.250 inches **Extended Washer Diameter:** Between 0.365 inches and 0.385 inches **Extended Washer Thickness:** 0.040 inches **First Diameter From Head:** Between 0.275 inches and 0.276 inches **Second Diameter From Head:** Between 0.142 inches and 0.146 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.485 inches and 0.495 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: Between 0.635 inches and 0.665 inches **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 **Externally Relieved Body Diameter Quantity:** Material: Nickel alloy **Material Specification:** Ams 5708 assn standard single material response **Thread Series Designator:** Unjf Shelf Life: N/a

--

Unit Of Measure:

NSN 5306-00-369-5725

Externally Relieved Body Bolt - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0