

View Online at <https://aerobasegroup.com/nsn/5306-00-369-5835>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.498 inches and 0.580 inches

**Fastener Length:**

Between 0.560 inches and 0.580 inches

**Head Style:**

Double hexagon w/hole

**Head Height:**

Between 0.250 inches and 0.270 inches

**Width Between Flats:**

Between 0.243 inches and 0.251 inches

**Extended Washer Diameter:**

Between 0.365 inches and 0.385 inches

**Extended Washer Thickness:**

Between 0.040 inches and 0.050 inches

**Shank Unthreaded Hole Diameter:**

0.065 inches first hole and 0.072 inches first hole

**Thread Diameter:**

0.190 inches

**Features Provided:**

Finished head

**Thready Qty Per Inch (tpi):**

32

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

0.435 inches first hole and 0.455 inches first hole

**Material:**

Nickel alloy

**Material Specification:**

Ams 5708 assn standard single material response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0