

View Online at <https://aerobasegroup.com/nsn/5306-00-369-5850>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.460 inches and 0.547 inches

**Fastener Length:**

Between 0.552 inches and 0.572 inches

**Head Style:**

Double hexagon w/hole

**Head Height:**

Between 0.248 inches and 0.268 inches

**Width Between Flats:**

0.250 inches

**Extended Washer Diameter:**

Between 0.365 inches and 0.385 inches

**Extended Washer Thickness:**

0.040 inches

**End Application:**

Engine, aircraft, f100-pw-100 (f-15a/b/c/d)pumper; engine, aircraft f100-pw-229 (f15e, f16c/d); aircraft, f-16; aircraft, f-111; aircraft, eagle f-15; navstar global positioning system user equipment (ue); support equipment, c-5 aircraft; engine, aircraft, f100-pw-200 (f-16a/b/c/d); engine, aircraft, f100 pw220 (f-15c/d/e)

**Thread Diameter:**

0.190 inches

**Grip Length:**

Between 0.025 inches and 0.092 inches

**Features Provided:**

Finished head

**Thready Qty Per Inch (tpi):**

32

**Material:**

Titanium alloy

**Material Specification:**

Ams 4967 assn standard single material response

**Surface Treatment:**

Anodize

**Surface Treatment Specification:**

Pwa 37-1, fscm 77445 mfr ref single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0