

View Online at <https://aerobasegroup.com/nsn/5306-00-369-5850>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.460 inches and 0.547 inches

Fastener Length:

Between 0.552 inches and 0.572 inches

Head Style:

Double hexagon w/hole

Head Height:

Between 0.248 inches and 0.268 inches

Width Between Flats:

0.250 inches

Extended Washer Diameter:

Between 0.365 inches and 0.385 inches

Extended Washer Thickness:

0.040 inches

End Application:

Engine, aircraft, f100-pw-100 (f-15a/b/c/d)pumper; engine, aircraft f100-pw-229 (f15e, f16c/d); aircraft, f-16; aircraft, f-111; aircraft, eagle f-15; navstar global positioning system user equipment (ue); support equipment, c-5 aircraft; engine, aircraft, f100-pw-200 (f-16a/b/c/d); engine, aircraft, f100 pw220 (f-15c/d/e)

Thread Diameter:

0.190 inches

Grip Length:

Between 0.025 inches and 0.092 inches

Features Provided:

Finished head

Thready Qty Per Inch (tpi):

32

Material:

Titanium alloy

Material Specification:

Ams 4967 assn standard single material response

Surface Treatment:

Anodize

Surface Treatment Specification:

Pwa 37-1, fscm 77445 mfr ref single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0