

View Online at <https://aerobasegroup.com/nsn/5306-00-369-6064>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.630 inches and 0.650 inches

**Fastener Length:**

1.400 inches

**Head Style:**

Flat chamfer

**Head Diameter:**

0.499 inches

**Head Height:**

Between 0.253 inches and 0.273 inches

**Shank Unthreaded Hole Diameter:**

0.076 inches first hole and 0.086 inches first hole

**Internal Drive Style:**

Hexagon

**Thread Diameter:**

0.375 inches

**Width Across Flats:**

Between 0.250 inches and 0.253 inches

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

170000 pounds per square inch

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

1.230 inches first hole and 1.290 inches first hole

**Surface Finish:**

32.0 microinches sides of head

**Material:**

Stainless steel

**Material Specification:**

17-4ph fms-0131, fscm 81755 mfr ref single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Mil-s-5002 military specification single treatment response

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-s-5002 spec.