

View Online at <https://aerobasegroup.com/nsn/5306-00-369-6064>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.630 inches and 0.650 inches

Fastener Length:

1.400 inches

Head Style:

Flat chamfer

Head Diameter:

0.499 inches

Head Height:

Between 0.253 inches and 0.273 inches

Shank Unthreaded Hole Diameter:

0.076 inches first hole and 0.086 inches first hole

Internal Drive Style:

Hexagon

Thread Diameter:

0.375 inches

Width Across Flats:

Between 0.250 inches and 0.253 inches

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

170000 pounds per square inch

Distance From Head Largest Bearing Surface To Shank Hole Center:

1.230 inches first hole and 1.290 inches first hole

Surface Finish:

32.0 microinches sides of head

Material:

Stainless steel

Material Specification:

17-4ph fms-0131, fscm 81755 mfr ref single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Mil-s-5002 military specification single treatment response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5002 spec.