## NSN 5306-00-371-4093



Ribbed Shoulder Bolt - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5306-00-371-4093 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 1.375 inches **Fastener Length:** Between 2.312 inches and 2.328 inches **Head Style:** Flat chamfer **Head Diameter:** 0.875 inches **Head Height:** Between 0.417 inches and 0.427 inches **Shoulder Diameter:** 0.554 inches first shoulder and 0.564 inches first shoulder **Shoulder Length:** 0.750 inches first shoulder **Rib Major Diameter:** Between 0.612 inches and 0.622 inches Rib Length: 0.750 inches Distance From Largest Diameter Of Bearing Surface Of Head To Ribs: 0.062 inches **Thread Diameter:** 0.562 inches **Features Provided:** Casehardened Thready Qty Per Inch (tpi): 18 Hardness Rating: 32.1 rockwell c and 37.6 rockwell c **Shoulder Shape:** Ribbed first shoulder **Material Specification:** Astm a108 assn standard single material response **Thread Series Designator:** Unf Shelf Life: N/a

**Unit Of Measure:** 

## NSN 5306-00-371-4093

Ribbed Shoulder Bolt - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0