

View Online at <https://aerobasegroup.com/nsn/5306-00-373-2927>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.715 inches and 0.815 inches

**Fastener Length:**

Between 6.050 inches and 6.080 inches

**Head Style:**

Double hexagon w/hole

**Head Height:**

Between 0.494 inches and 0.514 inches

**Width Between Flats:**

Between 0.553 inches and 0.564 inches

**Extended Washer Diameter:**

Between 0.818 inches and 0.828 inches

**Extended Washer Thickness:**

Between 0.113 inches and 0.133 inches

**Grip Diameter:**

Between 0.4985 inches and 0.4995 inches

**Thread Diameter:**

0.500 inches

**Grip Length:**

Between 5.240 inches and 5.260 inches

**Thready Qty Per Inch (tpi):**

20

**Min. Tensile Strength (psi):**

220000 pounds per square inch

**Material:**

Steel

**Material Specification:**

H-11 stsbs002, fscm 98897 mfr ref single material response

**Surface Treatment Specification:**

Ams 2416 assn standard single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0