## NSN 5306-00-373-3262

Machine Bolt - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5306-00-373-3262



**Thread Class:** 3a **Thread Direction: Right-hand Thread Length:** Between 0.620 inches and 0.735 inches Fastener Length: Between 0.740 inches and 0.760 inches Head Style: Double hexagon w/hole **Head Height:** Between 0.248 inches and 0.268 inches Width Between Flats: 0.250 inches **Extended Washer Diameter:** Between 0.365 inches and 0.385 inches **Extended Washer Thickness:** 0.040 inches Hole Diameter: 0.047 inches **Thread Diameter:** 0.190 inches Grip Length: Between 0.025 inches and 0.120 inches **Hole Quantity:** 4 Hole Type: Drilled **Features Provided:** Finished head Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch Hole Configuration Style: Hexagon flats Material: Titanium alloy **Material Specification:** Ams 4967 assn standard single material response **Surface Treatment:** Anodize

## NSN 5306-00-373-3262

Machine Bolt - Page 2 of 2



Surface Treatment Specification:

Pwa 37-1, fscm 77445 mfr ref single treatment response

## Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0