Thread Class:

1

Internally Relieved Body Bolt - Page 1 of 2





3a **Thread Direction: Right-hand Thread Length:** 0.275 inches **Fastener Length:** Between 1.335 inches and 1.345 inches **Head Style:** Flat fillister **Head Diameter:** Between 1.465 inches and 1.470 inches **Head Height:** Between 0.127 inches and 0.133 inches Hole Diameter: Between 0.470 inches and 0.480 inches **Shoulder Diameter:** Between 0.974 inches and 0.976 inches Shoulder Length: Between 1.000 inches and 1.020 inches **Concentric Hole Diameter:** Between 0.470 inches and 0.480 inches **End Application:** P&w f-100, p-100 eng **Thread Diameter:** 0.9375 inches **Hole Quantity:** Hole Type: Drilled Thready Qty Per Inch (tpi): 16 Hardness Rating: 35.0 rockwell c and 40.0 rockwell c Hole Configuration Style: Round longitudinal hole **Special Features:** Internal hole configuration has across recess shape as well as the 0.470-0.480 in. Dia.; original name-bolt, special Material: Steel comp 601 **Material Specification:** Ams6304 assn standard single material response

Internally Relieved Body Bolt - Page 2 of 2

Style Designator:

Concentric hole unthreaded

Thread Series Designator:

Unj

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0

