

View Online at <https://aerobasegroup.com/nsn/5306-00-382-7546>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.658 inches and 0.718 inches

Fastener Length:

Between 3.428 inches and 3.448 inches

Head Style:

Hexagon

Head Height:

Between 0.240 inches and 0.260 inches

Width Between Flats:

Between 0.679 inches and 0.690 inches

First Diameter From Head:

Between 0.368 inches and 0.375 inches

Second Diameter From Head:

Between 0.307 inches and 0.311 inches

Distance From Largest Bearing Surface Of Head To End Of First Diameter:

Between 0.480 inches and 0.520 inches

Distance From Largest Bearing Surface Of Head To End Of Second Diameter:

Between 2.730 inches and 2.770 inches

Thread Diameter:

0.375 inches

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

125000 pounds per square inch

Hardness Rating:

26.0 rockwell c and 32.0 rockwell c

Externally Relieved Body Diameter Quantity:

2

Special Features:

Head has 2 slots 180 degrees apart 0.130 in. Min 0.140 in. Maximum w

Material:

Steel comp 8740

Material Specification:

Ams 6322 assn standard single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Ams 2400 assn standard single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0