

View Online at <https://aerobasegroup.com/nsn/5306-00-382-7546>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.658 inches and 0.718 inches

**Fastener Length:**

Between 3.428 inches and 3.448 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.240 inches and 0.260 inches

**Width Between Flats:**

Between 0.679 inches and 0.690 inches

**First Diameter From Head:**

Between 0.368 inches and 0.375 inches

**Second Diameter From Head:**

Between 0.307 inches and 0.311 inches

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

Between 0.480 inches and 0.520 inches

**Distance From Largest Bearing Surface Of Head To End Of Second Diameter:**

Between 2.730 inches and 2.770 inches

**Thread Diameter:**

0.375 inches

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

125000 pounds per square inch

**Hardness Rating:**

26.0 rockwell c and 32.0 rockwell c

**Externally Relieved Body Diameter Quantity:**

2

**Special Features:**

Head has 2 slots 180 degrees apart 0.130 in. Min 0.140 in. Maximum w

**Material:**

Steel comp 8740

**Material Specification:**

Ams 6322 assn standard single material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Ams 2400 assn standard single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0