## NSN 5306-00-382-7586

Machine Bolt - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5306-00-382-7586



## **Thread Class:** 3a **Thread Direction: Right-hand Thread Length:** Between 0.337 inches and 0.419 inches Fastener Length: Between 0.775 inches and 0.795 inches **Head Style:** Hexagon **Head Height:** Between 0.110 inches and 0.125 inches Width Between Flats: Between 0.367 inches and 0.376 inches **Shank Unthreaded Hole Diameter:** 0.065 inches first hole and 0.072 inches first hole **Thread Diameter:** 0.190 inches **Features Provided:** Finished head Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch Distance From Head Largest Bearing Surface To Shank Hole Center: 0.615 inches first hole and 0.635 inches first hole Material: Titanium alloy **Material Specification:** Ams 4967 assn standard single material response Surface Treatment: Anodize **Surface Treatment Specification:** Pwa 37, fscm 77445 mfr ref single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a Unit Of Measure: **Demilitarization:** No

## **NSN 5306-00-382-7586** Machine Bolt - Page 2 of 2

Fiig: A003b0

