

View Online at <https://aerobasegroup.com/nsn/5306-00-385-9192>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.315 inches and 0.325 inches

**Fastener Length:**

1.625 inches

**Head Style:**

Dee chamfer

**Head Diameter:**

0.690 inches

**Head Height:**

0.100 inches

**Distance From Centerline To Flat:**

Between 0.290 inches and 0.295 inches

**Shank Unthreaded Hole Diameter:**

0.105 inches first hole and 0.108 inches first hole

**Concentric Hole Depth:**

1.160 inches

**Concentric Hole Diameter:**

Between 0.205 inches and 0.215 inches

**Thread Diameter:**

0.375 inches

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

180000 pounds per square inch

**Minimum Yield Strength:**

150000 pounds per square inch

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

1.470 inches first hole

**Special Features:**

Color white federal standard 595 no. 17875

**Material:**

Steel comp e4340

**Material Specification:**

Mil-s-5000, cond c military specification single material response

**Surface Treatment:**

Cadmium grip

**Surface Treatment Specification:**

Mms-420 fscm 76301 mfr ref single treatment response head

**Style Designator:**

Concentric hole unthreaded

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-s-5000 spec.