

View Online at <https://aerobasegroup.com/nsn/5306-00-385-9192>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.315 inches and 0.325 inches

Fastener Length:

1.625 inches

Head Style:

Dee chamfer

Head Diameter:

0.690 inches

Head Height:

0.100 inches

Distance From Centerline To Flat:

Between 0.290 inches and 0.295 inches

Shank Unthreaded Hole Diameter:

0.105 inches first hole and 0.108 inches first hole

Concentric Hole Depth:

1.160 inches

Concentric Hole Diameter:

Between 0.205 inches and 0.215 inches

Thread Diameter:

0.375 inches

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

180000 pounds per square inch

Minimum Yield Strength:

150000 pounds per square inch

Distance From Head Largest Bearing Surface To Shank Hole Center:

1.470 inches first hole

Special Features:

Color white federal standard 595 no. 17875

Material:

Steel comp e4340

Material Specification:

Mil-s-5000, cond c military specification single material response

Surface Treatment:

Cadmium grip

Surface Treatment Specification:

Mms-420 fscm 76301 mfr ref single treatment response head

Style Designator:

Concentric hole unthreaded

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5000 spec.