

View Online at <https://aerobasegroup.com/nsn/5306-00-385-9200>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.289 inches and 0.325 inches

Fastener Length:

Between 0.575 inches and 0.595 inches

Head Style:

Double hexagon w/hole

Head Height:

Between 0.293 inches and 0.313 inches

Width Between Flats:

Between 0.309 inches and 0.317 inches

Extended Washer Diameter:

Between 0.428 inches and 0.448 inches

Extended Washer Thickness:

Between 0.060 inches and 0.070 inches

First Diameter From Head:

Between 0.248 inches and 0.250 inches

Second Diameter From Head:

Between 0.142 inches and 0.146 inches

Distance From Largest Bearing Surface Of Head To End Of First Diameter:

Between 0.080 inches and 0.086 inches

Distance From Largest Bearing Surface Of Head To End Of Second Diameter:

Between 0.270 inches and 0.286 inches

Thread Diameter:

0.190 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

175000 pounds per square inch

Hardness Rating:

34.0 rockwell c and 44.0 rockwell c

Minimum Yield Strength:

115000 pounds per square inch

Externally Relieved Body Diameter Quantity:

2

Material:

Nickel alloy

Material Specification:

Ams 5708 assn standard single material response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0