NSN 5306-00-390-1538

Shoulder Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-390-1538 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.467 inches and 0.507 inches **Fastener Length:** Between 0.802 inches and 0.822 inches **Head Style:** Hexagon **Head Height:** Between 0.110 inches and 0.125 inches Width Between Flats: Between 0.367 inches and 0.376 inches **Shoulder Diameter:** 0.217 inches first shoulder and 0.218 inches first shoulder **Shoulder Length:** 0.315 inches first shoulder and 0.335 inches first shoulder **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 130000 pounds per square inch Hardness Rating: 24.0 rockwell c and 35.0 rockwell c Minimum Yield Strength: 85000 pounds per square inch **Shoulder Shape:** Round first shoulder Material: Iron alloy 660 **Material Specification:** As7477 assn standard single material response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:**

Demilitarization: No

NSN 5306-00-390-1538 Shoulder Bolt - Page 2 of 2



Fiig:

A003b0