
NSN 5306-00-390-1717

Shear Bolt - Page 1 of 2

Thread Class:





3a **Thread Direction: Right-hand Thread Length:** Between 0.760 inches and 0.820 inches Fastener Length: Between 1.880 inches and 1.940 inches Head Style: Double hexagon w/hole **Head Height:** 0.348 inches Width Between Flats: Between 0.368 inches and 0.377 inches **Extended Washer Diameter:** Between 0.521 inches and 0.531 inches **Extended Washer Thickness:** 0.082 inches Hole Diameter: 0.055 inches **Grip Diameter:** Between 0.3110 inches and 0.3120 inches **Thread Diameter:** 0.312 inches Grip Length: 1.120 inches **Hole Quantity:** 4 Hole Type: Drilled Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 175000 pounds per square inch Minimum Yield Strength: 115000 pounds per square inch Hole Configuration Style: Double hexagon longitudinal hole Material: Nickel alloy **Material Specification:**

Ams 5708 assn standard single material response

NSN 5306-00-390-1717

Shear Bolt - Page 2 of 2

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0

