

View Online at <https://aerobasegroup.com/nsn/5306-00-393-3634>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.938 inches

Fastener Length:

4.625 inches

Head Style:

Flat chamfer

Head Diameter:

0.875 inches

Head Height:

0.438 inches

Shank Unthreaded Hole Diameter:

0.141 inches first hole

First Diameter From Head:

0.490 inches

Second Diameter From Head:

0.560 inches

Third Diameter From Head:

0.490 inches

Distance From Largest Bearing Surface Of Head To End Of First Diameter:

0.875 inches

Distance From Largest Bearing Surface Of Head To End Of Second Diameter:

2.875 inches

Distance From Largest Bearing Surface Of Head To End Of Third Diameter:

3.688 inches

Thread Diameter:

0.562 inches

Thready Qty Per Inch (tpi):

18

Minimum Yield Strength:

105000 pounds per square inch

Distance From Head Largest Bearing Surface To Shank Hole Center:

4.344 inches first hole

Externally Relieved Body Diameter Quantity:

2

Special Features:

With groove in side of head 0.188 in. W 0.094 in. Deep, furnished with hex nut and cotter pin

Material:

Steel

Material Specification:

Mil-s-890, alloy mo. 2 military specification single material response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0

Mil-std (military Standard):

Mil-s-890 spec.