NSN 5306-00-395-1645

Externally Relieved Body Bolt - Page 1 of 1



| View Online at https://aerobasegroup.com/nsn/5306-00-395-1645 |
|--|
| Thread Class: |
| 3a |
| Thread Length: |
| 1.375 inches |
| Fastener Length: |
| 4.875 inches |
| Head Height: |
| 0.375 inches |
| Distance From Centerline To Flat: |
| 0.438 inches |
| Shank Unthreaded Hole Diameter: |
| 0.156 inches first hole |
| First Diameter From Head: |
| Between 0.681 inches and 0.683 inches |
| Second Diameter From Head: |
| Between 0.6872 inches and 0.6875 inches |
| Third Diameter From Head: |
| Between 0.681 inches and 0.683 inches |
| Distance From Largest Bearing Surface Of Head To End Of First Diameter: |
| 0.625 inches |
| Distance From Largest Bearing Surface Of Head To End Of Second Diameter: |
| 2.625 inches |
| Distance From Largest Bearing Surface Of Head To End Of Third Diameter: |
| 3.500 inches |
| Distance From Head Largest Bearing Surface To Shank Hole Center: |
| 4.625 inches first hole |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A003b0 |
| |