## NSN 5306-00-395-7273

Externally Relieved Body Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-395-7273 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.215 inches and 0.275 inches **Fastener Length:** Between 0.961 inches and 0.981 inches **Head Style:** Double hexagon w/hole **Head Height:** Between 0.248 inches and 0.268 inches Width Between Flats: 0.250 inches **Extended Washer Diameter:** Between 0.365 inches and 0.385 inches **Extended Washer Thickness:** 0.040 inches **First Diameter From Head:** Between 0.244 inches and 0.246 inches **Second Diameter From Head:** Between 0.142 inches and 0.146 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.556 inches and 0.576 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: Between 0.706 inches and 0.746 inches **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 Hardness Rating: 30.0 rockwell c and 38.0 rockwell c **Externally Relieved Body Diameter Quantity:** 2 Material: Steel **Material Specification:** Ams 6304 assn standard single material response **Surface Treatment:** 

Chromium

**Surface Treatment Specification:** 

Ams 2406 assn standard single treatment response

## NSN 5306-00-395-7273

Externally Relieved Body Bolt - Page 2 of 2



Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A003b0