

View Online at <https://aerobasegroup.com/nsn/5306-00-395-7273>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.215 inches and 0.275 inches

Fastener Length:

Between 0.961 inches and 0.981 inches

Head Style:

Double hexagon w/hole

Head Height:

Between 0.248 inches and 0.268 inches

Width Between Flats:

0.250 inches

Extended Washer Diameter:

Between 0.365 inches and 0.385 inches

Extended Washer Thickness:

0.040 inches

First Diameter From Head:

Between 0.244 inches and 0.246 inches

Second Diameter From Head:

Between 0.142 inches and 0.146 inches

Distance From Largest Bearing Surface Of Head To End Of First Diameter:

Between 0.556 inches and 0.576 inches

Distance From Largest Bearing Surface Of Head To End Of Second Diameter:

Between 0.706 inches and 0.746 inches

Thread Diameter:

0.190 inches

Thready Qty Per Inch (tpi):

32

Hardness Rating:

30.0 rockwell c and 38.0 rockwell c

Externally Relieved Body Diameter Quantity:

2

Material:

Steel

Material Specification:

Ams 6304 assn standard single material response

Surface Treatment:

Chromium

Surface Treatment Specification:

Ams 2406 assn standard single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0