NSN 5306-00-400-5740

Shear Bolt - Page 1 of 2

Thread Class:

За



View Online at https://aerobasegroup.com/nsn/5306-00-400-5740

Thread Direction:
Right-hand
Thread Length:
Between 0.731 inches and 0.751 inches
Fastener Length:
1.616 inches
Head Style:
Double hexagon w/hole
Head Height:
0.435 inches
Width Between Flats:
Between 0.492 inches and 0.502 inches
Extended Washer Diameter:
Between 0.740 inches and 0.750 inches
Extended Washer Thickness:
0.099 inches
Hole Diameter:
0.046 inches
Grip Diameter:
Between 0.4360 inches and 0.4370 inches
Thread Diameter:
0.438 inches
Grip Length:
Between 2.115 inches and 2.135 inches
Hole Quantity:
1
Hole Type:
Drilled
Thready Qty Per Inch (tpi):
20
Min. Tensile Strength (psi):
180000 pounds per square inch
Hardness Rating:
39.0 rockwell c and 43.0 rockwell c
Hole Configuration Style:
Hexagon longitudinal hole
Material:
Steel comp 8740 or steel comp e4340 or steel comp 4340 or steel comp 6150 or steel comp 4140
Surface Treatment:
Cadmium and chromate

NSN 5306-00-400-5740

Shear Bolt - Page 2 of 2



Surface Treatment Spec	ific	ation:
------------------------	------	--------

Qq-p-416, type 2, cl 3 federal specification all treatment responses

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

No

Fiig:

A003b0