NSN 5306-00-401-0828



Shoulder Bolt - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5306-00-401-0828 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.313 inches and 0.363 inches **Fastener Length:** Between 0.511 inches and 0.541 inches **Head Style:** Dished hexagon **Head Height:** Between 0.110 inches and 0.125 inches Width Between Flats: Between 0.367 inches and 0.376 inches **Shoulder Diameter:** 0.2172 inches first shoulder and 0.2182 inches first shoulder **Shoulder Length:** 0.178 inches first shoulder and 0.198 inches first shoulder **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch **Hardness Rating:** 36.0 rockwell c and 40.0 rockwell c **Shoulder Shape:** Round first shoulder Material: Steel comp 4140 or steel comp e4340 or steel comp 6150 or steel comp 8735 or steel comp 8740 **Material Specification:** Mil-s-5626 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-8503 military specification 3rd material response or mil-s-6098 military specification 4th material response or mil-s-6049 military specification 5th material response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:**

Fiig: A003b0

No

Demilitarization:

NSN 5306-00-401-0828

Shoulder Bolt - Page 2 of 2



Mil-std (military Standard):

Mil-s-5626 spec.