NSN 5306-00-401-4595

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-401-4595

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.475 inches and 0.525 inches
Fastener Length:
Between 0.985 inches and 1.015 inches
Head Style:
Double hexagon w/hole
Head Height:
0.254 inches
Width Between Flats:
Between 0.304 inches and 0.313 inches
Extended Washer Diameter:
Between 0.465 inches and 0.475 inches
Extended Washer Thickness:
0.042 inches
Hole Diameter:
0.037 inches
Grip Diameter:
Between 0.2485 inches and 0.2495 inches
Thread Diameter:
0.250 inches
Grip Length:
Between 0.490 inches and 0.510 inches
Hole Quantity:
4
Hole Type:
Drilled
Thready Qty Per Inch (tpi):
28
Min. Tensile Strength (psi):
220000 pounds per square inch
Hardness Rating:
46.0 rockwell c and 50.0 rockwell c
Hole Configuration Style:
Hexagon longitudinal hole
Material:
Steel comp h11
Material Specification:
Ams 6485 assn standard single material response or ams6487 assn standard single material response

NSN 5306-00-401-4595

Shear Bolt - Page 2 of 2

Fiig: A003b0



Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416, type 2, cl 3 federal specification all treatment responses
Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No