# NSN 5306-00-401-4599

Shear Bolt - Page 1 of 2

**Thread Class:** 

View Online at https://aerobasegroup.com/nsn/5306-00-401-4599



### 3a **Thread Direction: Right-hand Thread Length:** Between 0.586 inches and 0.636 inches Fastener Length: Between 1.471 inches and 1.501 inches Head Style: Double hexagon w/hole **Head Height:** 0.319 inches Width Between Flats: Between 0.367 inches and 0.376 inches **Extended Washer Diameter:** Between 0.575 inches and 0.585 inches **Extended Washer Thickness:** 0.050 inches Hole Diameter: 0.055 inches **Grip Diameter:** Between 0.3110 inches and 0.3120 inches **Thread Diameter:** 0.312 inches Grip Length: Between 0.865 inches and 0.885 inches **Hole Quantity:** 4 Hole Type: Drilled Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 260000 pounds per square inch Hardness Rating: 51.0 rockwell c and 54.0 rockwell c Hole Configuration Style: Hexagon longitudinal hole **Product Name:** Navy special project Material: Steel comp h11

# NSN 5306-00-401-4599

Shear Bolt - Page 2 of 2



### Material Specification:

Ams 6485 assn standard single material response or ams6487 assn standard single material response

### Surface Treatment:

Cadmium

Surface Treatment Specification:

Mil-c-8837, type2, cl 2 military specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

**Demilitarization:** No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-8837 spec.