

View Online at <https://aerobasegroup.com/nsn/5306-00-401-4992>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.227 inches

**Fastener Length:**

0.562 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.172 inches and 0.204 inches

**Width Between Flats:**

Between 0.490 inches and 0.502 inches

**Shoulder Diameter:**

0.3112 inches first shoulder and 0.3117 inches first shoulder

**Shoulder Length:**

0.240 inches first shoulder and 0.250 inches first shoulder

**Hole Diameter:**

0.070 inches

**Thread Diameter:**

0.190 inches

**Hole Quantity:**

6

**Hole Type:**

Drilled

**Thready Qty Per Inch (tpi):**

32

**Hole Configuration Style:**

Double hexagon flats

**Criticality Code Justification:**

Aatn

**Shoulder Shape:**

Round first shoulder

**Material:**

Steel comp 4140 or steel comp 8740 or steel comp 8630 or steel comp 8735 or steel comp 4130 or steel comp 4037

**Material Specification:**

Mil-s-5626 military specification 1st material response or mil-s-6049 military specification 2nd material response or mil-s-6050 military specification 3rd material response or mil-s-6098 military specification 4th material response or mil-s-6758 military specification 5th material response or ams 6300 assn standard 6th material response

**Surface Treatment:**

Cadmium

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-s-5626 spec.