## NSN 5306-00-401-5236

Close Tolerance Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-401-5236 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.505 inches and 0.572 inches **Fastener Length:** Between 2.515 inches and 2.562 inches **Head Style:** Hexagon **Head Height:** Between 0.172 inches and 0.204 inches Width Between Flats: Between 0.490 inches and 0.502 inches **Hole Diameter:** 0.070 inches **Grip Diameter:** Between 0.3112 inches and 0.3117 inches **Shank Unthreaded Hole Diameter:** 0.076 inches and 0.081 inches first hole **Thread Diameter:** 0.312 inches **Grip Length:** Between 1.990 inches and 2.010 inches **Hole Quantity:** 1 **Hole Type:** Drilled Thready Qty Per Inch (tpi): 24 Hardness Rating: 24.0 rockwell c and 44.0 rockwell c **Hole Configuration Style:** Hexagon longitudinal hole Distance From Head Largest Bearing Surface To Shank Hole Center: 2.343 inches and 2.375 inches first hole **Surface Finish:** 32.0 microinches grip **Product Name:** Navy special project

Material:

Iron alloy 660

## NSN 5306-00-401-5236

Close Tolerance Bolt - Page 2 of 2



Material Specification:
-------------------------

Ams 5732 assn standard single material response

**Thread Series Designator:** 

Unf

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0