## NSN 5306-00-402-5691

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-402-5691 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.553 inches and 0.603 inches **Fastener Length:** Between 4.313 inches and 4.343 inches **Head Style:** Hexagon **Head Height:** Between 0.188 inches and 0.203 inches Width Between Flats: Between 0.553 inches and 0.564 inches **Grip Diameter:** Between 0.3740 inches and 0.3745 inches **Shank Unthreaded Hole Diameter:** 0.106 inches first hole and 0.116 inches first hole **Thread Diameter:** 0.375 inches **Grip Length:** Between 3.740 inches and 3.760 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 160000 pounds per square inch Distance From Head Largest Bearing Surface To Shank Hole Center: 4.102 inches first hole and 4.152 inches first hole Material: Titanium alloy uns r56400 **Material Specification:** Ams4967 assn standard single material response **Thread Series Designator:** Unjf **Specification Data:** 80205-nas676 professional/industrial association standard Shelf Life: N/a **Unit Of Measure:** 

No

**Demilitarization:** 

## NSN 5306-00-402-5691

Shear Bolt - Page 2 of 2



Fiig:

A003b0