

View Online at <https://aerobasegroup.com/nsn/5306-00-402-8850>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.366 inches and 0.448 inches

Fastener Length:

Between 0.428 inches and 0.448 inches

Head Style:

Double hexagon w/hole

Head Height:

Between 0.250 inches and 0.270 inches

Width Between Flats:

Between 0.243 inches and 0.251 inches

Extended Washer Diameter:

Between 0.365 inches and 0.385 inches

Extended Washer Thickness:

Between 0.040 inches and 0.050 inches

Hole Diameter:

0.070 inches

Shank Unthreaded Hole Diameter:

0.060 inches first hole and 0.080 inches first hole

Thread Diameter:

0.190 inches

Hole Quantity:

4

Hole Type:

Drilled

Features Provided:

Finished head

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

130000 pounds per square inch

Hardness Rating:

248.0 brinell standard and 341.0 brinell standard

Minimum Yield Strength:

85000 pounds per square inch

Hole Configuration Style:

Round

Distance From Head Largest Bearing Surface To Shank Hole Center:

0.340 inches first hole and 0.350 inches first hole

Surface Finish:

63.0 microinches bearing surface of head

Material:

Iron alloy 660

Material Specification:

Ams 5735 assn standard single material response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0