NSN 5306-00-402-9060

Machine Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-402-9060 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.514 inches and 0.574 inches **Fastener Length:** Between 4.029 inches and 4.059 inches **Head Style:** Hexagon **Head Height:** Between 0.140 inches and 0.172 inches Width Between Flats: Between 0.430 inches and 0.439 inches **Thread Diameter:** 0.250 inches **Grip Length:** Between 3.485 inches and 3.515 inches **Features Provided:** Finished head Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 140000 pounds per square inch Material: Iron alloy 660 **Material Specification:** Ams 5732 assn standard 1st material response or ams 5737 assn standard 2nd material response or ams 5733 assn standard 3rd material response **Surface Treatment: Passivate Surface Treatment Specification:** Mil-s-5002 military specification single treatment response **Thread Series Designator:** Unf **Specification Data:** 80205-nas1004 professional/industrial association standard Shelf Life: N/a **Unit Of Measure:**

No

Demilitarization:

NSN 5306-00-402-9060

Machine Bolt - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5002 spec.