## NSN 5306-00-403-6670

Machine Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-403-6670

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.339 inches and 0.359 inches
Fastener Length:
0.438 inches
Head Style:
Hexagon
Head Height:
0.250 inches
Width Between Flats:
Between 0.430 inches and 0.439 inches
Hole Diameter:
0.070 inches
Thread Diameter:
0.250 inches
Grip Length:
Between 0.079 inches and 0.099 inches
Hole Quantity:
6
Hole Type:
Drilled
Features Provided:
Finished head
Finished head  Thready Qty Per Inch (tpi):
Thready Qty Per Inch (tpi):
Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi):
Thready Qty Per Inch (tpi): 28  Min. Tensile Strength (psi): 130000 pounds per square inch
Thready Qty Per Inch (tpi): 28  Min. Tensile Strength (psi): 130000 pounds per square inch Hardness Rating:
Thready Qty Per Inch (tpi): 28  Min. Tensile Strength (psi): 130000 pounds per square inch Hardness Rating: 248.0 brinell standard and 341.0 brinell standard
Thready Qty Per Inch (tpi): 28  Min. Tensile Strength (psi): 130000 pounds per square inch  Hardness Rating: 248.0 brinell standard and 341.0 brinell standard  Minimum Yield Strength:
Thready Qty Per Inch (tpi):  28  Min. Tensile Strength (psi):  130000 pounds per square inch  Hardness Rating:  248.0 brinell standard and 341.0 brinell standard  Minimum Yield Strength:  85000 pounds per square inch
Thready Qty Per Inch (tpi):  28  Min. Tensile Strength (psi):  130000 pounds per square inch  Hardness Rating:  248.0 brinell standard and 341.0 brinell standard  Minimum Yield Strength:  85000 pounds per square inch  Hole Configuration Style:
Thready Qty Per Inch (tpi):  28  Min. Tensile Strength (psi):  130000 pounds per square inch  Hardness Rating:  248.0 brinell standard and 341.0 brinell standard  Minimum Yield Strength:  85000 pounds per square inch  Hole Configuration Style:  Hexagon flats
Thready Qty Per Inch (tpi):  28  Min. Tensile Strength (psi):  130000 pounds per square inch  Hardness Rating:  248.0 brinell standard and 341.0 brinell standard  Minimum Yield Strength:  85000 pounds per square inch  Hole Configuration Style:
Thready Qty Per Inch (tpi):  28  Min. Tensile Strength (psi):  130000 pounds per square inch  Hardness Rating:  248.0 brinell standard and 341.0 brinell standard  Minimum Yield Strength:  85000 pounds per square inch  Hole Configuration Style:  Hexagon flats  Surface Finish:
Thready Qty Per Inch (tpi):  28  Min. Tensile Strength (psi):  130000 pounds per square inch  Hardness Rating:  248.0 brinell standard and 341.0 brinell standard  Minimum Yield Strength:  85000 pounds per square inch  Hole Configuration Style:  Hexagon flats  Surface Finish:  32.0 microinches threads  Material:
Thready Qty Per Inch (tpi):  28  Min. Tensile Strength (psi):  130000 pounds per square inch  Hardness Rating:  248.0 brinell standard and 341.0 brinell standard  Minimum Yield Strength:  85000 pounds per square inch  Hole Configuration Style:  Hexagon flats  Surface Finish:  32.0 microinches threads

## NSN 5306-00-403-6670

Machine Bolt - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0