## NSN 5306-00-404-6355

Internal Wrenching Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-404-6355

| a   |  |
|---|--|
| u la                                |  |
| hread Direction:  |  |
| light-hand  |  |
| bread Length:   |  |
| .625 inches   |  |
| astener Length:   |  |
| .250 inches   |  |
| lead Diameter:  |  |
| Between 1.859 inches and 1.875 inches                                   |  |
| lead Height:  |  |
| Between 1.230 inches and 1.250 inches                                   |  |
| irst Diameter From Head:  |  |
| Setween 1.069 inches and 1.074 inches                                   |  |
| Distance From Largest Bearing Surface Of Head To End Of First Diameter: |  |
| .625 inches   |  |
| nternal Drive Style:  |  |
| lexagon   |  |
| hread Diameter:   |  |
| .250 inches   |  |
| Vidth Across Flats:   |  |
| Between 0.875 inches and 0.880 inches                                   |  |
| hready Qty Per Inch (tpi):  |  |
|   |  |
| Product Name:   |  |
| lavy special project  |  |
| pecial Features:  |  |
| apered threads  |  |
| laterial:   |  |
| steel   |  |
| laterial Specification:   |  |
| stm a193, gr b16 assn standard single material response                 |  |
| Surface Treatment:  |  |
| Copper  |  |
| hread Series Designator:  |  |
| In  |  |
| shelf Life:   |  |
| I/a   |  |
| Init Of Measure:  |  |
|   |  |
| Demilitarization:   |  |
| lo  |  |

## **NSN 5306-00-404-6355** Internal Wrenching Bolt - Page 2 of 2

Fiig: A003b0

