

View Online at <https://aerobasegroup.com/nsn/5306-00-405-5621>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

0.690 inches

Fastener Length:

2.000 inches

Head Style:

Hexagon

Head Height:

Between 0.226 inches and 0.243 inches

Width Between Flats:

Between 0.551 inches and 0.562 inches

First Diameter From Head:

Between 0.369 inches and 0.375 inches

Second Diameter From Head:

0.250 inches

Distance From Largest Bearing Surface Of Head To End Of First Diameter:

0.100 inches

Distance From Largest Bearing Surface Of Head To End Of Second Diameter:

1.310 inches

Thread Diameter:

0.375 inches

Thready Qty Per Inch (tpi):

24

Externally Relieved Body Diameter Quantity:

2

Material:

Steel comp 301 or steel comp 302 or steel comp 303 or steel comp 303f or steel comp 303se or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 308 or steel comp 309 or steel comp 309s or steel comp 310 or steel comp 310s or steel comp 314 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 323 or steel comp 324 or steel comp 347 or steel comp 348 or steel comp 385

Material Specification:

66 federal standard all material responses

Surface Treatment:

Passivate

Surface Treatment Specification:

Gps20-200 type 1, fscm 24930 mfr ref single treatment response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0