NSN 5306-00-405-6162



Shoulder Bolt - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5306-00-405-6162 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.367 inches and 0.448 inches **Fastener Length:** Between 2.463 inches and 2.493 inches **Head Style:** Hexagon **Head Height:** Between 0.172 inches and 0.204 inches Width Between Flats: Between 0.490 inches and 0.502 inches **Shoulder Diameter:** 0.3090 inches first shoulder and 0.3120 inches first shoulder **Shoulder Length:** 2.010 inches first shoulder and 2.025 inches first shoulder **Shank Unthreaded Hole Diameter:** 0.076 inches first hole and 0.086 inches first hole **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 180000 pounds per square inch Distance From Head Largest Bearing Surface To Shank Hole Center: 2.275 inches first hole and 2.325 inches first hole **Shoulder Shape:** Round first shoulder Material: Iron alloy 660 **Material Specification:** Ams 5737 assn standard single material response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

No

NSN 5306-00-405-6162 Shoulder Bolt - Page 2 of 2



Fiig:

A003b0