

View Online at <https://aerobasegroup.com/nsn/5306-00-408-3484>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.346 inches and 0.396 inches

Fastener Length:

Between 0.740 inches and 0.760 inches

Head Style:

Double hexagon w/hole

Head Height:

Between 0.320 inches and 0.340 inches

Width Between Flats:

Between 0.304 inches and 0.313 inches

Extended Washer Diameter:

Between 0.428 inches and 0.448 inches

Extended Washer Thickness:

Between 0.060 inches and 0.070 inches

Shoulder Diameter:

0.2470 inches first shoulder and 0.2480 inches first shoulder

Shoulder Length:

0.312 inches first shoulder and 0.322 inches first shoulder

Thread Diameter:

0.190 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

125000 pounds per square inch

Hardness Rating:

26.0 rockwell c and 32.0 rockwell c

Shoulder Shape:

Round first shoulder

Material:

Stainless steel

Material Specification:

Ams 6320 assn standard single material response or ams 6322 assn standard single material response or ams 6327 assn standard single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Ams 2400 assn standard single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0