NSN 5306-00-410-1749

Shoulder Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-410-1749 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.325 inches **Fastener Length:** Between 0.627 inches and 0.647 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.295 inches and 0.315 inches **Head Height:** Between 0.045 inches and 0.055 inches **Shoulder Diameter:** 0.217 inches first shoulder and 0.218 inches first shoulder **Shoulder Length:** 0.302 inches first shoulder and 0.322 inches first shoulder **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 **Hardness Rating:** 28.0 rockwell c and 35.0 rockwell c **Shoulder Shape:** Round first shoulder Material: Steel comp 4130 or steel comp 8630 or steel comp 8735 or steel comp 8740 **Material Specification:** Mil-s-6758 military specification 1st material response or mil-s-6050 military specification 2nd material response or mil-s-6098 military specification 3rd material response or mil-s-6049 military specification 4th material response **Surface Treatment:** Cadmium or chromate **Surface Treatment Specification:** Qq-p-416 type 2 cl 3 federal specification single treatment response **Thread Series Designator:** Unjf **Specification Data:**

N/a

Unit Of Measure:

Shelf Life:

81205-bacb30kk manufacturers standard

NSN 5306-00-410-1749

Shoulder Bolt - Page 2 of 2



_						
11	em)	 tor	172	+ 1	nn	

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-6758 spec.