

View Online at <https://aerobasegroup.com/nsn/5306-00-410-6968>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.899 inches and 0.939 inches

**Fastener Length:**

Between 2.284 inches and 2.304 inches

**Head Style:**

Double hexagon w/hole

**Head Height:**

0.618 inches

**Width Between Flats:**

Between 0.679 inches and 0.690 inches

**Extended Washer Diameter:**

Between 1.040 inches and 1.050 inches

**Extended Washer Thickness:**

0.150 inches

**Hole Diameter:**

0.055 inches

**Grip Diameter:**

Between 0.6230 inches and 0.6240 inches

**Thread Diameter:**

0.625 inches

**Grip Length:**

Between 1.365 inches and 1.385 inches

**Hole Quantity:**

4

**Hole Type:**

Drilled

**Thready Qty Per Inch (tpi):**

18

**Min. Tensile Strength (psi):**

180000 pounds per square inch

**Hardness Rating:**

39.0 rockwell c and 43.0 rockwell c

**Hole Configuration Style:**

Round

**Material:**

Steel comp e4340 or steel comp 4340 or steel comp 8740 or steel comp 6150 or steel comp 4140

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416, type 2, cl 3 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0