

View Online at <https://aerobasegroup.com/nsn/5306-00-411-1172>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

1.500 inches

**Eye Inside Diameter:**

Between 0.250 inches and 0.256 inches

**Shank Length:**

2.440 inches

**Eye Stock Thickness:**

0.400 inches

**Shank Unthreaded Hole Diameter:**

0.062 inches first hole and 0.065 inches first hole

**Overall Length:**

3.045 inches

**Thread Diameter:**

0.375 inches

**Thready Qty Per Inch (tpi):**

16

**Min. Tensile Strength (psi):**

125000 pounds per square inch

**Distance From Center Of Eye To Shank End:**

2.721 inches

**Distance From Threaded End To Shank Hole Center:**

2.315 inches first hole

**Eye Outside Width:**

0.562 inches

**Material:**

Steel comp 4130 or steel comp 8630 or steel comp 8735 or steel comp 8740

**Material Specification:**

Mil-s-6758 military specification 1st material response or mil-s-6050 military specification 2nd material response or mil-s-6098 military specification 3rd material response or mil-s-6049 military specification 4th material response

**Surface Treatment:**

Cadmium

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0

**Mil-std (military Standard):**

Mil-s-6758 spec.